

251 BAY FOX P.I.G.

CAPACITY

MAX. WEIGHT CAPACITY	1200			
PERSONS (QUANTITY)	8			
PERSONS (LBS.)	2200			
MAX H.P.	300	HP	224	KW

SPECIFICATION

L.O.A.	292	IN	24'-4"/ 7.41	FT/M
L.O.A.	309	IN	25'-10"/ 12.17	FT/M
BEAM	102	IN	8'-6"/2.59	FT/M
DEAD RISE	15	DEG		
TRANSOM ANGLE	15	DEG		
TRANSOM HEIGHT(Center line)	25	IN	0.64	METER
TRANSOM WIDTH	99.5	IN	2.53	METER
COCKPIT DEPTH AFT	18	IN	0.46	METER
COCKPIT DEPTH BOW	21	IN	0.53	METER
FREEBOARD AFT	22.5	IN	0.57	METER
FREEBOARD BOW	27	IN	0.69	METER
DRAFT	13	IN	0.33	METER
DEPTH	40.5	IN	1.03	METER
CENTER OF GRAVITY FROM KEEL/TRANSOM	73	IN	1.85	METER
HEIGHT, KEEL TO TOP (LIGHT FOLDED)	106	IN	2.69	METER
BRIDGE CLEARANCE HARD TOP	93	IN	2.36	METER
CABIN HEIGHT (HEAD)	58	IN	1.47	METER
CENTER OF GRAVITY FROM TRANSOM	42	IN	1.07	METER
DRY WEIGHT BOAT: w/ options but no Gear, Batteries, Fluids, or Motor(s)	2940	LBS.	1334	KG
MAX. WEIGHT BOAT: w/ Fluids, batteries,: But no Gear or Motor(s)	4520	LBS.	2050	KG
MAX. WEIGHT BOAT: w/batteries, Fluids, gear, largest Motor(s)	4645	LBS.	2107	KG
BATTERY QUANTITY	1 std / 1 opt	EA	1-H-ENG, 1 BACKUP	
TROLLING BATTERIES	3	EACH	3 BATT FOR 36V	
TROLLING MOTOR LENGTH (BOW)	54	IN	1.37	METER
PANEL SIZE FOR ELECTRONICS	22W x 11H (SINGLE MACHINE ONLY)			

TUB CAPACITY

ROPE LOCKER	4.32	CF	51"Lx33.5"Wx23"D	
TUB BOW CENTER TOP	180	QT	24"Lx34"Wx14"D	
TUB BOW CENTER STEP	80	QT	16"Lx34"Wx9"D	
TUB BOW PORT/ ROD	4.5	CF	54"Lx13"Wx11"D	
TUB BOW STARBOARD	140	QT	57"Lx13"Wx11"D	
TUB BOW FLOOR (bucket)	40	QT	15"Lx14"Wx 14"D	
TUB CONSOLE BAITWELL	12	GAL	22Wx14Lx13d	
TUB LEANPOST BAITWELL	20	GAL	12"Lx26"Wx17"D	
TUB BAITWELL AFT	30	GAL	15"Lx36"Wx 13"D	
TUB COOLER PORT AFT	65	QT	15.5"Lx23"Wx11"D	
TUB COOLER STBD AFT	65	QT	15.5"Lx23"Wx11"D	
COOLER SIZE (REMOVABLE) (only with Aluminum Lean post)	72	QT	IGLOO	

TANK CAPACITY

FUEL TANK	77	GAL	291	LITER
FUEL SENDER	10"	INCH	NA	NA
FRESH WATER	6	GAL	23	LITER
HOLDING TANK	NA	GAL	NA	LITER