

268 Commander P.I.G.

CAPACITY

MAX. WEIGHT CAPACITY	YACHT CERTIFICATION			
PERSONS (QUANTITY) (SEATING FOR 12)	YACHT CERTIFICATION			
PERSONS (LBS.)	YACHT CERTIFICATION			
MAX H.P.	450	HP	336	KW

SPECIFICATION

L.O.A.	312	IN	26'-0"/ 7.9M	FT/M
L.W.L.	248	IN	20'-6"/ 6.3	FT/M
BEAM	111	IN	9'-3"/ 2.8M	FT/M
DEAD RISE	20	DEG		
DEAD RISE BOW ENTRY POINT	38	DEG		
TRANSOM ANGLE	15	DEG		
STATIC FLOAT ANGLE (KEEL TO BOW)	0	DEG		
TRANSOM HEIGHT(Center line)	30 (25 @ engine)	IN	0.76	METER
TRANSOM WIDTH	103	IN	2.62	METER
COCKPIT DEPTH AFT	27	IN	0.69	METER
COCKPIT DEPTH BOW	34	IN	0.86	METER
FREEBOARD AFT	35	IN	0.89	METER
FREEBOARD BOW (BOW TO WATER LINE TROLLING MOTOR)	49	IN	1.24	METER
DRAFT	16	IN	0.41	METER
DEPTH	62	IN	1.57	METER
CENTER OF GRAVITY FROM KEEL/TRANSOM	108	IN	2.74	METER
WATERLINE BEAM	95.625	IN	2.43	METER
WATERLINE LENGTH	244.375	IN	6.21	METER
HEIGHT, KEEL TO TOP (LIGHT FOLDED)	118	IN	3.00	METER
BRIDGE CLEARANCE W/TOP	102	IN	2.59	METER
CABIN HEIGHT	67	IN	1.70	METER
DRY WEIGHT BOAT: w/ options but no Gear, Batteries, Fluids, or Motor(s)	4535	LBS.	2057	KG
WEIGHT BOAT (Options and Motor(s) no Fluids)	5765	LBS.	2615	KG
MAX. WEIGHT BOAT: w/batteries, Fluids, gear, largest Motor(s)	7644	LBS.	3467	KG
BATTERY QUANTITY	3	EA	1-LE/H,1-RE,,1-BKP	
PANEL SIZE FOR ELECTRONICS	15.5 W x 16 H (single or dual 10" Garmin)			

TUB CAPACITY

ROPE LOCKER	12	CF	32"L, 60"W,28"D	
TUB BOW PORT	78	QT	38"L, 13"W, 13"D	
TUB BOW STARBOARD	78	QT	38"L, 13"W, 13"D	
TUB BOW FLOOR (bucket)	40	QT	15"L,14"W, 14"D	
TUB CONSOLE LOUNGER	7	CF	26"L, 35"W, 17"D	
TUB FISH AFT PORT	117	QT	60"L, 14"W, 11"D	
TUB FISH AFT STBD	117	QT	60"L, 14"W, 11"D	
TUB BAITWELL PORT	30	GAL	20"L, 18"W, 24"D	
TUB COOLER/ DAY ANCHOR -AFT OF GATE	56	QT	16"L,15"W, 15"D	
COOLER SIZE (REMOVABLE)	65	QT	ARTIC	

TANK CAPACITY

FUEL TANK	139	GAL	526	LITER
FUEL SENDER	17	INCH	NA	NA
FRESH WATER	12	GAL	45	LITER
HOLDING TANK	12	GAL	45	LITER